

FOREVER GmbH Robert-Bosch-Str. 43, 68542 Heddesheim, Germany **Phone:** +49 (0) 62 03/930 20 - 0 **Fax:** +49 (0) 62 03/930 20 - 40 **E-mail:** info@forever-ots.com **Web:** www.forever-ots.com

Tanas fan Instructions fan

Transfer Instructions for:

FOREVER Laser Dark (No-Cut)

for BLACK AND DARK COLORED TEXTILES



PRINT SETTINGS: (Only for OKI Printers working with White Toner)

- Paper and Print Settings: Ultra Heavy 2, Multi Purpose-Tray
- White-Toner Darkness: (Calibration in the Printer Menu): -3
- Image Mode: Mirror Image, CMYK Mode (not RGB), Color Print, White On



TRANSFER SETTINGS:

	AUTOMATIC HEAT PRESS	MANUAL HEAT PRESS
PRESSURE	variable	variable
TEMPERATURE	180-200°C (356-392°F)	180-200°C (356-392°F)
TIME	30 Seconds	30 Seconds



TRANSFER APPLICATION:

- Print your design in mirror image mode onto the A-Paper.
- Place the B-Paper on top of the lower plate and place the A-Paper on the top of the B-Paper.
- Press all together at 200°C (392°F) for 60 sec. for A4 and 75 sec. for A3 with 3-4 bar pressure.
- Open the press, turn the papers around immediately, so that now the A-Paper is at the bottom. Rub strongly
 with a piece of textile over the transfer to guarentee a flat position. Leave the papers on the lower plate while
 you seperate them. Seperate the B-paper from the A-Paper while still hot in one slowly, fluent move.
- Cut around the design to avoid a coating frame.
- Place the textile or another substrate on the lower plate of the heat press.
- Fix the transfer with heat-resistant tape, to prevent an unintended hot peel, while you open the press.
- Press the transfer. (Settings in the chart) below.
- Remove the backing paper after it is absolutely cold.
- For an matt screen printed look, press the garment with a sheet of Matt Finish Economy for 5 seconds.

DECORATING WITH HOT STAMPING FOILS (Hot Stamping Foils)

- Place the Hot Stamping Foil on your image and cover it with 5 sheets of normal paper.
- **Press** it by 200°C (392°F) for 30-45 seconds with high pressure.
- Peel off the Hot Stamping Foil when completely cold.
- Press the T-Shirt again with Matt Finish Economy for 5 seconds!
- Rub strongly with a piece of textile to remove unnecessary areas of the hot stamping foils.



WASHING:

• Up to 40°C (warm wash cycle).



IRONING:

• When ironing cover the print with baking paper.

MATERIAL	°C	°F	DRUCK	ZEIT	WASCHEN
Cotton	180-200°C	356-392°F	3-4 Bar	30 Sek.	Up to 40°C
Polyester	130°C	266°F	3-4 Bar	40 Sek.	Up to 40°C
Leather	120°C	248°F	1-2 Bar	30 Sek.	
Nylon	150°C	302°F	2-3 Bar	30 Sek.	Up to 30°C
Carton	100°C	212°F	1-2 Bar	20 Sek.	



Before starting a mass production, we recommend to make transfer and washing test with all materials.



Important advice for double-sided printing on textiles:

T-Shirts for a **double-sided print** (frontside & backside), has to be put over the lower heat plate. In this case only one side will be treated with heat and you avoid that the applicated design from the other side will be pressed out again.